



기호	변경 사항	날 짜	서 명
①			
②			
③			
④			

AT MAXIMUM EFFICIENCY						
MOTOR GEAR	HD3448A(12VDC)		HD3448B(24VDC)		HD3448C(24VDC)	
	RPM	Kg·Cm	RPM	Kg·Cm	RPM	Kg·Cm
1/022	227.2	1.3	227.2	1.3	340.9	1.4
1/034	147.0	2.0	147.0	2.0	220.5	2.2
1/043	116.2	2.5	116.2	2.5	174.4	2.8
1/050	100.0	2.9	100.0	2.9	150.0	3.3
1/062	80.6	3.6	80.6	3.6	120.9	4.0
1/068	73.5	4.0	73.5	4.0	110.2	4.5
1/083	60.2	4.8	60.2	4.8	90.3	5.4
1/105	47.6	6.1	47.6	6.1	71.4	6.9
1/116	43.1	6.7	43.1	6.7	64.6	7.6
1/162	30.8	8.5	30.8	8.5	46.2	9.5
1/182	27.5	9.2	27.5	9.2	41.2	10.8
1/204	24.5	10.7	24.5	10.7	36.7	12.0
1/240	20.8	12.6	20.8	12.6	31.2	14.1
1/308	16.2	16.1	16.2	16.1	24.3	18.1
1/350	14.2	20	14.2	20	21.4	20
1/452	11.0	20	11.0	20	16.6	20
1/615	8.1	20	8.1	20	12.1	20
1/687	7.2	20	7.2	20	10.9	20

No	DESCRIPTION	Q'TY	재질	사양	비고
단위 : mm	3각법	척도	품명 (기종)	HDSG56-3448	
설계	검수	승인			
			관련업체	관련기종(완제품)	
(주)한일모텍		도번			